

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

41674

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/856851

INTERNATIONAL APPLICATION NO.
PCT/EP99/09061INTERNATIONAL FILING DATE
November 24, 1999PRIORITY DATE CLAIMED
November 27, 1998TITLE OF INVENTION
COMMUTATION DEVICE, ESPECIALLY A COMMUTATOR, AND METHOD FOR PRODUCING SUCH A DEVICEAPPLICANT(S) FOR DO/EO/US
ARMIN WAGNER; CLAUDIA WISINGER; DIETER MICHAEL ROTH; MICHAEL EIGNER; ECKHARD KONIG

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☒ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
Translation of Preliminary Examination Report

ATTORNEY'S DOCKET NUMBER
41674

U.S. APPLICATION NO (if known, see 37 CFR 1.51)
097 85685 1

INTERNATIONAL APPLICATION NO
PCT/EP99/09061

ATTORNEY'S DOCKET NUMBER
41674

17. ☒ The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO	\$1,000.00
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO	\$860.00
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO	\$710.00
International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)	\$690.00
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)	\$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

CALCULATIONS PTO USE ONLY

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	9 - 20 =	0	X \$18.00
Independent claims	3 - 3 =	0	X \$80.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable)	+ \$270.00
---	------------

TOTAL OF ABOVE CALCULATIONS	=	\$ 860.00
------------------------------------	----------	------------------

Reduction of 1/2 for filing by small entity, if applicable.

SUBTOTAL =

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(f)). ☐ +

TOTAL NATIONAL FEE	=	\$ 860.00
---------------------------	----------	------------------

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **\$40.00** per property

TOTAL FEES ENCLOSED	=	\$ 900.00
----------------------------	----------	------------------

Amount to be refunded:	\$
charged:	\$

- a. ☒ A check in the amount of \$ 900.00 to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 18-2220. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.


SEND ALL CORRESPONDENCE TO

Roylance, Abrams, Berdo & Goodman, L.L.P.

1300 19th Street, N.W., Suite 600

Washington, D.C. 20036

(202) 659-9076


SIGNATURE

SIGNATURE

Mark S. Bicks

NAME _____

28.770

REGISTRATION NUMBER

41674

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of :
: ARMIN WAGNER ET AL. : PATENT
: :
Serial No.: NEW : Group Art Unit:
: :
Filed: Herewith : Examiner:
: :
For: COMMUTATION DEVICE, ESPECIALLY :
A COMMUTATOR, AND METHOD FOR :
PRODUCING SUCH A DEVICE :

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Preliminary to examination and calculation of the filing fee, please amend the above-identified application, as amended in preliminary examination, as follows:

In the Claims

3. A device as specified in Claim 1 , wherein the segments (304) are additionally fastened on the outer cover (303) by a bonding layer (305).

4. A device as specified in Claim 1 , wherein the bonding agent (5; 105; 205; 305) is an adhesive layer, preferably an adhesive layer of an epoxy resin, polyurethane resin, or phenol resin.


7. A device as specified in Claim 5 , wherein a circular segmental disk (104) consisting of carbon or containing carbon is fastened by a bonding agent (105) on the frontal surface of the connection means (103') facing away from the outer cover (103), and the segmental disk (104) is isolated relative to the axis of rotation (102) by radial cuts in the segments (104; 204).

8. A device as specified in Claim 1 , wherein the bonding agent (5; 105; 205; 305) is a soldered or welded layer, in particular a soft, hard, or glass solder layer or an ultrasound, friction, or electrode welded layer.

REMARKS

The above changes eliminate multiple dependency in the claims.

Respectfully submitted,



Mark S. Bicks
Reg. No. 28,770

Roylance, Abrams, Berdo & Goodman, L.L.P.
1300 19th Street, N.W.
Washington, D.C. 20036
(202) 659-9076

Dated: May 24, 2001

Marked-up version of original claims

2

of its end facing away from the segmental surface (308) and extending over the plane of the front surface of the outer cover (303).

3. A device as specified in Claim 1 ~~or 2~~, wherein the segments (304) are additionally fastened on the outer cover (303) by a bonding layer (305).

4. A device as specified in ~~one of~~ Claims 1 to 3, wherein the bonding agent (5; 105; 205; 305) is an adhesive layer, preferably an adhesive layer of an epoxy resin, polyurethane resin, or phenol resin.

5. A device for current reversal, in particular a commutator (101; 201) with a preformed, more or less cylindrical outer cover (103; 203) having an axis of rotation (102; 202) and electrically conductive current reversal or commutator segments (104; 204) which may be fastened on connection means (103'; 203') mounted between the segments (104; 204) and the outer cover (103; 203) by means of a bonding agent (105; 205), the outer cover (103; 203) and the segments (104; 204) having interactive means for positioning and orienting the segments (104; 204) relative to the outer cover (103; 203), characterized in that there is mounted, in the frontal bottom surface of the cupshaped connection means (103'), a recess (106) shaped as a keyhole into which a corresponding projection (107), in the shape of a matching pin or bar, of a preformed outer cover core is inserted

and as a result the connection means (103') is fastened on the preformed outer cover core by clamping action.

6. A device as specified in Claim 5, wherein the electric connection means (103') is fastened to the outer cover (103') by means of an electrically insulating or an electrically conductive bonding layer (103"), for example, by an adhesive, soldered, or welded layer.

7. A device as specified in Claim 5 or ~~6~~, wherein a circular segmental disk (104) consisting of carbon or containing carbon is fastened by a bonding agent (105) on the frontal surface of the connection means (103') facing away from the outer cover (103), and the segmental disk (104) is isolated relative to the axis of rotation (102) by radial cuts in the segments (104; 204).

8. A device as specified in ~~one of Claims 1 to 7~~, wherein the bonding agent (5; 105; 205; 305) is a soldered or welded layer, in particular a soft, hard, or glass solder layer or an ultrasound, friction, or electrode welded layer.

9. A process for manufacture of a current reverser, a commutator in particular (1; 101; 201) as specified in one of Claims 1 to 8, wherein a plurality, preferably all, of the segments (4; 104; 204; 304) to be fastened to the outer cover (3; 103; 203; 303) are delivered simultaneously to the outer cover (3; 103; 203; 303).

4/PRTS

09/856851

JC18 Rec'd PCT/PTC 25 MAY 2001

WO 00/33428

PCT/EPP99/09061

Commutation device,
especially a commutator,
and method for producing such a device

This invention relates to a current reversal device, a commutator in particular, and to a process for production of such a device. Such devices are employed especially in electric motors and current generators, as for example in tools powered by electricity, actuating drives, or fuel pumps.

Generic devices in this category are disclosed, for example, in DE 41 37 400 C2. In this instance a composite segment is stamped from a rolled or drawn copper strip and then is roller burnished, split a short distance or scored, and sprayed with a compression molding compound which after setting forms the outer cover of the commutator. Then the bore in the outer cover must be machined and the clasps of the commutator segments bent for fastening the ends of the windings. After an additional scaling or stripping procedure the commutators undergo electrical testing and are then mounted on the engine shaft by force fitting.

In addition, DE 195 30 051 A1 discloses a plug-in commutator in which the commutator segments are inserted into an assembly cage and then sprayed with molded plastic material to form the outer cover. These operations are followed by additional machining and testing steps carried out to comply with the requirements set for accuracy of the geometric dimensions of the commutator and for the stability of the latter.

DE-OS-2 352 155 discloses a commutator for a miniature electric motor and a process for manufacture of this motor, in which a desired number of commutator plates are fastened on a jacket surface of a core in specific sectors by means of an adhesive.

State-of-the-art commutators require a large number of production and testing steps in order to make it possible to guarantee the required degrees of accuracy and reliability.

Hence it is the object of the invention to develop a commutator which exhibits high accuracy with respect to its geometric dimensions and high long-term stability and is also simple to manufacture.

The object is attained by means of the device and process disclosed in the independent claims. Special embodiments of the invention are disclosed in the subsidiary claims.

According to Claim 1, the segments may be fastened on the outer cover by fastening means mounted more or less between the outer cover and the segments. The outer cover is generally made from an electrically insulating material, in particular a plastic such as a duroplastic, a thermoplastic, or a ceramic material. Consideration may be given as an alternative also to a metal outer cover such as one of aluminum whose surface is provided with a preferably electrically insulating coating such as a coating of varnish or a layer of metal oxide which may also be produced by oxidation of the metal outer cover. The outer cover may also be built up in two or more layers, and especially may have a flexible internal hub surrounded by a temperature-stable outer shell on which the segments may be fastened. The flexible internal hub provides for the necessary force fitting for mounting the commutator on an engine shaft. The commutator segments generally consist of copper or a copper compound; consideration may be

given alternatively also to other materials in keeping with the requirements set for conductivity, temperature stability, and chemical resistance. The fastening means is preferably applied in layers between the segments and the outer cover and may be applied prior to fastening on the outer cover and/or the segments.

The outer cover and the segments have interacting means for positioning and orienting the segments relative to the outer cover. They may be made in the form of punctiform, linear, or planiform projections and matching recesses on the outer cover or on the segments. The segments, for example, may have studlike projections which may be inserted into matching grooves oriented parallel to the axis of rotation on the circumference of the outer cover. In the case of a planar commutator, radially oriented studs on a frontal surface may fit into corresponding recesses or grooves on the pertinent segment or the cylindrical outer cover may have on the edge on its front side an axially projecting and preferably circumferentially annular continuous projection which ensures centering of the disk segment to be fastened on the front surface, which disk segment may then be divided into individual commutator segments electrically insulated from each other.

If the fastening means is a layer of adhesive, this layer may be filled with suitable additives meeting electric and/or thermal requirements. The thermal coefficient of linear expansion of the adhesive layer, for example, can be reduced by a ceramic filler. If required, an electrically conductive metal filler, such as one based on Ag, Cu, or Ni may be used to establish a connection between the segment and the outer cover, for example, if the outer cover for a planar commutator comprises electrically conductive segmental connecting lines. The fillers may in particular define a distance between the commutator segments and the outer cover and so the

thickness of the adhesive layer, preferably by means of spherical fillers, especially ones in the form of glass or ceramic spheres. The layer thickness ranges, for example, from 20 to 250 μm and preferably from 50 to 100 μm . The layer thickness may also be determined in advance by means of spacers, preferably in one piece, made up of the outer cover or the commutator segments, as for example by punctate, linear, or planiform projections. The adhesive to be selected or treated is one such as will absorb as little moisture as possible after setting, one which will form a permanent strong bond with copper in particular and is dimensionally stable when subjected to mechanical and/or thermal stress.

If the fastener is a soldered or welded layer, the commutator possesses particularly high temperature stability and chemical resistance. Consideration is given in this case preferably to low melting soft, hard, or glass solders, such as low melting lead/tin solders or glass solders with a high lead oxide content. An especially low bonding temperature is obtained by ultrasound or friction welding.

If the segments and the outer cover have force fitted interacting anchor and receiving means, the segments may be inserted into the outer cover and the spring loaded anchor and receiving means operating in opposition to each other form a sufficiently stable clamp connection. In addition, the segments on the outer cover may be positioned by the bonding means. It is also possible, however, to dispense with an additional bonding agent and to position the segments exclusively with anchor and receiving means forming a clamp connection. Both the segments and the outer cover may have only anchor means or only receiving means or a combination of anchor and receiving means. The sole essential requirement is that anchor or

receiving means of the segment interact with receiving or anchor means of the outer cover.

It is especially advantageous for it to be possible to insert or clip the segments radially into the outer cover, as for example in the case of a drum commutator, or to insert them axially into a frontal surface of the outer cover, in the case of a planar commutator, for example.

It is also advantageous for positioning and orienting of the segments to take place simultaneously with insertion of the segments into the outer cover by means of the anchor or receiving means. Means for positioning and orienting extend preferably parallel to the axis of rotation along a peripheral surface or radially to the axis of rotation along a frontal surface of the outer cover. All suitable configurations, in particular studs which are triangular, rectangular, hemispherical, or swallow-tailed in cross-section, may be considered as positioning and orienting means. Cross-sectional shapes which widen out in depth, and especially ones provided with a point for ease of insertion, are particularly well suited for anchoring.

In the process claimed for the invention segments are fastened to the outer cover by means of a bonding agent mounted more or less between the outer cover and the segments. For example, the outer cover as a whole may be immersed in a bonding means bath before the segments are fastened. Alternatively or in addition, at least the surface of the segments facing the outer cover may be provided with the bonding means. Optionally the surfaces of the outer cover and/or of the segments are to be cleaned and/or provided with a bonding agent before the fastener is applied. The surfaces may by preference be conditioned in a vacuum process, such as in an ion or plasma vacuum process. Surface treatment may also be carried out to achieve

adequate aging and corrosion resistance of the fastening layer to stresses during subsequent use and/or uniform wetting means with the fastener. Secondary treatment of the bonded joint is also advantageous in cementing in particular in order to prevent corrosion and/or infiltration and so reduction of the strength of the fastening.

Means for positioning and orienting the segments are provided whose shape is such that positioning and orienting take place automatically as the segments are delivered, for example grooves triangular in cross-section in the outer cover, into which studs of the segments of matching cross-section are introduced. In this case the fastening means may be introduced into the groove, for example, as a line of adhesive, before delivery. As the segments are subsequently delivered the fastening means is displaced to form a flat bonding layer between outer cover and segment.

If a clamp connection is established between anchor and receiving means, fastening means introduced between the outer cover and the segments may be dispensed with. In this instance fastening is effected exclusively by means of anchor and receiving means forming part of a clamp connection.

If fastening means is provided, an adhesive, solder, or weld layer is to be considered in particular for this purpose. The maximum temperature in additional treatment may be around 300 °C for a brief period. Setting of an adhesive layer should always take place at the lowest possible temperature, for example, in the temperature range from 50 to 250 °C, preferably from 170 to 200 °C.

If segments are delivered to the outer cover sequentially, this may be effected by step-by-step rotation of the outer cover around its axis of rotation and application of the segments piece by piece or by

rolling of the outer cover onto the segments interconnected in a strip, for example. In the case of step-by-step delivery the connection between the outer cover and the pertinent segment may be established either immediately after delivery or as the final step for all segments delivered together, for example, by surrounding the outer cover with segments in place with compression and/or heating tongs.

If all segments are delivered to the outer cover simultaneously, this may be accomplished with a suitable compression and/or heating tool, which following delivery ensures mechanically reliable fastening of the segments to the outer cover. It may be effected, for example, by pressing the segments into the outer cover, in particular by pressing the anchor and receiving means together and/or by heating the segments to the point of melting of the fastening means and production of a bonding layer.

Additional advantages, features, and details of the invention are to be found in the subsidiary claims and in the following description, in which several embodiments are described in detail with reference to the drawings. Each of the features referred to in the claims and in the description is an essential element of the invention, either individually or in any combination.

Figure 1 presents a cutaway side view of the commutator claimed for the invention,

Figure 2 various embodiments of the positioning means over section II-II in Figure 1,

Figure 3 a section through a planar commutator parallel to the axis of rotation,

Figure 4 a sectional view of an alternative embodiment of a planar commutator,

Figure 5 a view of the frontal surface of the planar commutator in Figure 3,

Figure 6 a blanked out flat commutator segment,

Figure 7 a possible method of assembly of the segment in Figure 6, and

Figure 8 the production process illustrated by a flow chart.

Figure 1 presents a side view of a cutaway commutator 1 as claimed for the invention. The more or less cylindrical outer cover 3 having an axis of rotation 2 consists preferably of a thermoplastic or duroplastic, such as a hollow cylinder of phenol resin produced by hot casting. Electrically insulated from each other over the circumference on the cylindrical outer wall and preferably containing copper or a copper compound are segments 4, whose ends are bent to form a hook for connection of the accompanying coil winding (not shown). The segments 4 are secured by fastening means 5 mounted more or less between them and the outer cover 3, in this instance by an adhesive layer of epoxy resin, polyurethane resin, or phenol resin. Shown in the lower half of Figure 1 is a second commutator segment 4' having two anchor means 4" oriented radially as one piece; it both increases the stability of fastening of the second segment 4' on the outer cover 3 and simultaneously performs the function of positioning and orienting the second segment 4'. The anchor means 4" engages corresponding recesses in the outer cover, which may be in the form, for example, of circumferential annular grooves 3' or circumferential annular shoulders 3". Fitted on the outer cover 3 is a cone 15 which

simplifies sliding of the outer cover 3 onto an engine shaft (not shown).

Figure 2 shows various embodiments of means for positioning, orienting, and anchoring segments 4 on the outer cover over section II-II in Figure 1. In figure section 2A segment 4a has two studs 4a' triangular in cross-section and extending parallel to the axis of rotation 2 (perpendicular to the plane of the drawing); these studs are either pressed into the outer cover 3 by application of force and/or under the influence of temperature or are inserted into suitably shaped grooves in the outer cover 3. Figure Section 2B shows a segment 4b with a single central stud 4b' also triangular in cross-section and extending parallel to the axis of rotation 2. Figure section 2C shows a segment 4c with an anchor element 4c' which initially extends as a stud and has on its end oriented toward the axis of rotation a thickened area more or less circular in cross-section. The anchor means 4c' may extend parallel to the axis of rotation 2 in the form of a stud over a part or over the entire axial length of the outer cover 3 or may be punctate, in the form of a mushroom, for example. In either case, the anchor means 4c' fits into a corresponding recess in the outer cover 3, which is elastically deformed in this area and applies a clamping force ensuring stable fastening of segment 4c. Figure section 2D with segment 4d and anchor means 4d' and figure section 2E with segment 4e and anchor means 4e', swallow-tailed in cross-section, show another two of the anchor means, which may be in virtually any configuration desired. Anchor means 4f' in figure section 2F, preferably forming a single piece with segment 4f, is configured from the viewpoint of geometry and material so that it is deformed initially when segment 4f is pressed into the outer cover 3 and when fully inserted fits into a more or less T-shaped recess in the outer cover 3. In this embodiment as well elastic deformation of the outer cover takes place in the area engaged; such

deformation applies the clamping force required for segment 4f. Figure section 2G shows a segment 4g bent radially on its longitudinal sides or suitably shaped, the two sides 4g' either fitting into corresponding recesses in the outer cover 3 or cutting into them as a result of application of force. Figure section 2H shows a segment 4h with a cross-section in the form of a circular segment, the segment being inserted into a corresponding recess in the outer cover 3. Figure sections 2A to 2H show only a selection of the large number of the positioning, orienting, and anchoring options for the segments 4 on the outer cover 3. The anchor means on the outer cover 3 and corresponding recesses or receiving means in the segments may, of course, be analogously shaped. In addition or as an alternative to the anchor means, fastening may also be effected by a bonding layer, such as an adhesive, solder, or weld layer.

Figure 3 shows a section through a planar commutator 101, with an outer cover 103 having an axis of rotation 102, which also comprises electric connection means 103' provided for connection of the coil windings which are to establish contact with segments 104 fastened on the frontal surface of the outer cover 103. If the outer cover 103 consists of an electrically insulating material, the connection between the outer cover 103 and the electric connection means 103' may be made in the form both of an electrically insulating and an electrically conducting bonding layer 103", such as an adhesive, solder, or welded layer. On the other hand, the connection 105 between electric connecting means 103' and segments 104 is to be established in all cases by means of an electrically conductive bonding layer 105, as for example by means of an adhesive layer filled with metal particles. The electric connection means 103' may initially be in the form of a copper cup spray coated preferably with a duroplastic to form the outer cover 103. Circular segment disk 104, preferably consisting of carbon or containing carbon, is fastened on

outer cover 103 as thus preformed by means of bonding layer 105. Electric insulation of the commutator segments is then effected by means of cuts through the segment disk which are radial relative to the axis of rotation 102 through segment disk 104 and through the frontal bottom surface of the copper cup of connecting means 103'.

Figure 4 illustrates another planar commutator 201 with an axis of rotation 202 and a bar-shaped connection means 203' which is a component of the outer cover 203. The bonding layer 205 between connection means 203' and carbon disk 204 is electrically conductive. The bonding layer 203" between connection means 203' and the outer cover 203 may be either electrically insulating or electrically conductive. An alternative embodiment of a copper planar commutator in which the copper planar segments 403' are fastened to an electrically insulating or electrically conductive adhesive layer 403" on the outer cover 403 is illustrated in the lower half of Figure 4.

Figure 5 presents a view of the frontal surface of the planar commutator over section V-V in Figure 3 with carbon disk 104 not yet fastened. In a segment area 103a there is provided in a bottom surface of the cupshaped connection means 103' a recess 106 shaped as a keyhole into which a matching pin-shaped or stud-shaped projection 107 of a preformed outer cover core may be inserted. In this way the connection means 103' may be fastened on the preformed outer cover core as an addition or as an alternative to bonding layer 103", in order to exert a clamping effect.

Figure 6 shows a punched out flat segment 304 of copper for a drum-type commutator which consists essentially of a rectangular segmental surface 308 proper from a narrow side of which project two external positioning and orienting means 309 and a central stud 310, the latter being provided for connection of the coil winding. A

positioning means 311 is also formed on the opposite narrow side. Each of positioning means 309, 311 has a projecting lug on its end. After the segment 304 has been provided with curvature matching that of the outer cover, the positioning means 309, 311 are bent to an angle of approximately 90° relative to segmental surface 308 in the direction of the arrow 312, as illustrated in Figure 7. The bent positioning means 309, 311 are introduced into corresponding receiving means in the outer cover 303 and are thereby positioned and oriented. Segment 304 may be fastened on outer cover 303 exclusively by clamping between positioning means 309, 311 and the outer cover 303, or alternatively or additionally by a bonding layer 305. The outer cover 303 consists for this purpose exclusively of a flexible core 314 which exerts a flexible clamping effect on segments 304 or positioning means 309, 311 and force fitting on the engine shaft (not shown). Externally the outer cover 304 has an outer shell 315 which extends radially relative to the axis of rotation 302 and is form and temperature stable. The right half of Figure 7 illustrates an alternative option of bending the positioning means 309, in which repeated bending forms a clasp 309' which is inserted into a matching recess in core 314; similarly (by a process not shown) the positioning means 311 on the opposite side may be inserted as a clasp.

A flow chart illustrating the production process is presented in Figure 8. Shaping of the outer cover and of the pertinent segments proceeds in parallel; both the outer cover and the segments are preferably cleaned with suitable solvents or cleaning agents before being placed in position, and if necessary a bonding agent is applied. Positioning of the segments on the outer cover may be carried out sequentially or simultaneously; in any event during the delivery the segments are oriented and positioned relative to the outer cover. Lastly, the segments are fastened on the outer cover by clamping,

[illegible]

CLAIMS

1. A device for current reversal, in particular a commutator (1; 101; 201) with a preformed, more or less cylindrical outer cover (3; 103; 203; 303) having an axis of rotation (2; 102; 202; 302) and electrically conductive current reversal or commutator segments (4; 104; 204; 304) which may be fastened on the outer cover (3; 103; 203; 303) by means of a bonding agent (5; 105; 205; 305) applied more or less between it and the segments (4; 104; 204; 304), *characterized in that* the outer cover (3; 103; 203; 303) and the segments (4; 104; 204; 304) have interactive means (3', 3", 4"; 4a"; 106, 107, 309, 311) for positioning and orienting the segments (4; 104; 204; 304) relative to the outer cover (3; 103; 203; 303).

2. A device as specified in Claim 1, *wherein* the bonding agent (5; 105; 205; 305) is an adhesive layer, preferably an adhesive layer of an epoxy resin, polyurethane resin, or phenol resin.

3. A device as specified in Claim 2, *wherein*, in a planar commutator (101; 201) the commutator segments (104; 204) may be fastened by means of an adhesive layer, the commutator segments (104; 204) preferably by means of an electrically conductive adhesive layer (105; 205) on pertinent connection means (103'; 203').

4. A device as specified in Claim 1, *wherein* the bonding agent (5; 105; 205; 305) is a soldered or welded layer, in particular a soft, hard, or glass solder layer or an ultrasound, friction, or electrode welded layer.

5. A device as specified in one of Claims 1 to 4, *wherein* the segments (4; 104; 204; 304) and the outer cover (3; 103; 203; 303) have frictionally connected interacting anchor and receiving means (4c'; 4d'; 4e').

6. A device as specified in Claim 5, *wherein* the anchor means (4c'; 4d'; 4e') and the pertinent receiving means on the outer cover (3; 103; 203; 303) are designed from the viewpoint of geometry and materials so that the segments (4; 104; 204; 304) may be inserted radially in relation to the axis of rotation (2; 102; 202; 302) into a circumferential surface or axially into a frontal surface of the outer cover (3; 103; 203; 303).

7. A device as specified in Claim 5 or 6, *wherein* the anchor means (4c'; 4d'; 4e') are formed by positioning and orienting means.

8. A device as specified in one of Claims 1 to 7, *wherein* the means (3', 3", 4"; 4a'; 106, 107; 309, 311) for positioning and orienting extend parallel to the axis of rotation along a circumferential surface of the outer cover (3; 103; 203; 303) and/or radially along a frontal surface of the outer cover (3; 103; 203; 303).

9. A device as specified in one of Claims 1 to 8, *wherein* a clamp connection between outer covers (3; 103; 203; 303) and segments (4; 104; 204; 304) may be produced by configuration of the means (3', 3", 4"; 4a"; 106; 107; 309, 311) on the basis of geometry and materials.

10. A process for manufacture of a current reversal means, a commutator in particular (1; 101; 201), comprising the steps:

- molding a more or less cylindrical outer cover (3; 103; 203; 303) having an axis of rotation (2, 102; 202; 302),
- molding electrically conductive current reversal or commutator segments (4; 104; 204; 304) which may be fastened on the outer cover (3; 103; 203; 303),
- delivery of the segments (4; 104; 204; 304), relative to the axis of rotation (2; 102; 202; 302), in a radial direction to a circumferential surface of the outer cover (3; 103; 203; 303) or in an axial direction to a frontal surface of the outer cover (3; 103; 203; 303),
- positioning and orienting the segments (4; 104; 204; 304) relative to the outer cover (3; 103; 203; 303) during delivery to the outer cover (3; 103; 203; 303) and the segments (4; 104; 204; 304) by interacting means (3', 3", 4"; 4a'; 106, 107; 309, 311) each preferably in one piece), and
- fastening of the segments (4; 104; 204; 304) on the outer cover (3; 103; 203; 303) by bonding means (5; 105; 205; 305) mounted more or less between the outer cover (3; 103; 203; 303) and the segments (4; 104; 204; 304).

11. A process as specified in Claim 10, wherein adhesion, soldering, or welding takes place between segments (4; 104; 204; 304) and outer cover (3; 103; 203; 303).

12. A process as specified in Claim 11, wherein, in the case of a planar commutator (101; 201) the commutator segments (104; 204) are fastened by means of an adhesive layer, commutator segments (104; 204), preferably containing carbon, by means of an electrically



conductive adhesive layer (105, 205) on accompanying connection means (103'; 203').

13. A process as specified in one of Claims 10 to 12 , *wherein*, during fastening, receiving means (4c'; 4d'; 4e') preferably molded on segments (4; 104; 204; 304) are clamped in corresponding receiving means, ones preferably molded on the outer cover (3; 103; 203; 303).

14. A process as specified in one of Claims 10 to 13, *wherein* the segments (4; 104; 204; 304) are delivered sequentially to the outer cover (3; 103; 203; 303).

15. A process as specified in one of Claims 10 to 13, *wherein* a plurality, preferably all, of the segments (4; 104; 204; 304) to be fastened on the outer cover (3; 103; 203; 303) are delivered to the outer cover (3; 103; 203; 303) simultaneously.

1 / 4






Fig. 3




Fig. 4




Fig. 5

3 / 4




Fig. 6




Fig. 7

4/4




FIGURE 8

PTO/SB/103 (8-96)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

Declaration and Power of Attorney for Patent Application

Erklärung für Patentanmeldungen mit Vollmacht

German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

daß mein Wohnsitz, meine Postanschrift und meine Staatsangehörigkeit den im nachstehenden nach meinem Namen aufgeführten Angaben entsprechen, daß ich nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent für die Erfindung mit folgendem Titel beantragt wird:

deren Beschreibung hier beigelegt ist, es sei denn (in diesem Falle Zutreffendes bitte ankreuzen), diese Erfindung

- ☐ wurde angemeldet am _____ unter der US-Anmeldenummer oder unter der Internationalen Anmeldenummer im Rahmen des Vertrags über die Zusammenarbeit auf dem Gebiet des Patentwesens (PCT) _____ und am _____ abgeändert (falls zutreffend).

Ich bestätige hiermit, daß ich den Inhalt der oben angegebenen Patentanmeldung, einschließlich der Ansprüche, die eventuell durch einen oben erwähnten Zusatzantrag abgeändert wurde, durchgesehen und verstanden habe.

Ich erkenne meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Titel 37, Code of Federal Regulations, § 1.56 von Belang sind.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COMMUTATION DEVICE, ESPECIALLY A COMMUTATOR, AND METHOD FOR PRODUCING SUCH A DEVICE

the specification of which is attached hereto unless the following box is checked:

- ☒ was filed on November 24, 1999 as United States Application Number or PCT International Application Number PCT/EP99/09061 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

[Page 1 of 3]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

PTO/SB/103 (8-96)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

German Language Declaration

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäß Title 35, US-Code, § 119 (a)-(d), bzw. § 365(b) aller unten aufgeführten Auslandsanmeldungen für Patente oder Erfinderurkunden, oder § 365(a) aller PCT internationalen Anmeldungen, welche wenigstens ein Land ausser den Vereinigten Staaten von Amerika benennen, und habe nachstehend durch ankreuzen sämtliche Auslandsanmeldungen für Patente bzw. Erfinderurkunden oder PCT internationale Anmeldungen angegeben, deren Anmeldetag dem der Anmeldung, für welche Priorität beansprucht wird, vorangeht.

Prior Foreign Applications
(Frühere ausländische Anmeldungen)

198 54 843.5 DE
(Number) (Country)
(Nummer) (Land)

(Number) (Country)
(Nummer) (Land)

Ich beanspruche hiermit Prioritätsvorteile unter Title 35, US-Code, § 119(e) aller US-Hilfsanmeldungen wie unten aufgezählt.

(Application No.) (Filing Date)
(Aktenzeichen) (Anmeldetag)

(Application No.) (Filing Date)
(Aktenzeichen) (Anmeldetag)

Ich beanspruche hiermit die mir unter Title 35, US-Code, § 120 zustehenden Vorteile aller unten aufgeführten US-Patentanmeldungen bzw. § 365(c) aller PCT internationalen Anmeldungen, welche die Vereinigten Staaten von Amerika benennen, und erkenne, insofern der Gegenstand eines jeden früheren Anspruchs dieser Patentanmeldung nicht in einer US-Patentanmeldung, bzw. PCT internationalen Anmeldung in in einer gemäß dem ersten Absatz von Title 35, US-Code, § 112 vorgeschriebenen Art und Weise offenbart wurde, meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Title 37, Code of Federal Regulations, § 1.56 von Belang sind und die im Zeitraum zwischen dem Anmeldetag der früheren Patentanmeldung und dem nationalen oder im Rahmen des Vertrags über die Zusammenarbeit auf dem Gebiet des Patentwesens (PCT) gültigen internationalen Anmeldetags bekannt geworden sind.

(Application No.) (Filing Date)
(Aktenzeichen) (Anmeldetag)

(Application No.) (Filing Date)
(Aktenzeichen) (Anmeldetag)

Ich erkläre hiermit, daß alle in der vorliegenden Erklärung von mir gemachten Angaben nach bestem Wissen und Gewissen der Wahrheit entsprechen, und ferner daß ich diese eidesstattliche Erklärung in Kenntnis dessen ablege, daß wissentlich und vorsätzlich falsche Angaben oder dergleichen gemäß § 1001, Title 18 des US-Code strafbar sind und mit Geldstrafe und/oder Gefängnis bestraft werden können und daß derartige wissentlich und vorsätzlich falsche Angaben die Rechtswirksamkeit der vorliegenden Patentanmeldung oder eines aufgrund deren erteilten Patentes gefährden können.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed
Priorität nicht beansprucht

27 November 1998
(Day/Month/Year Filed)
(Tag/Monat/Jahr der Anmeldung)



(Day/Month/Year Filed)
(Tag/Monat/Jahr der Anmeldung)



I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status) (patented, pending, abandoned)
(Status) (patentiert, schwebend, aufgegeben)

(Status) (patented, pending, abandoned)
(Status) (patentiert, schwebend, aufgegeben)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

PTO/SB/103 (8-96)

Approved for use through 9/30/98. OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

German Language Declaration

VERTRETUNGSVOLMACHT: Als benannter Erfinder beauftrage ich hiermit den (die) nachstehend aufgeführten Patentanwalt (Patentanwälte) und/oder Vertreter mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Angelegenheiten vor dem US-Patent- und Markenamt: (Name(n) und Registrationsnummer(n) auflisten)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: (list name and registration number)

David S. Abrams	Reg. No. 22,576	Lance G. Johnson	Reg. No. 32,531
Robert H. Berdo	Reg. No. 19,415	Dean H. Nakamura	Reg. No. 33,981
Alfred N. Goodman	Reg. No. 26,458	Stacey J. Longanecker	Reg. No. 33,952
Mark S. Bicks	Reg. No. 28,770	Joseph J. Buczynski	Reg. No. 35,084
John E. Holmes	Reg. No. 29,392		
Garrett V. Davis	Reg. No. 32,023		

Postanschrift:

Send Correspondence to:

Mark S. Bicks, Roylance, Abrams, Berdo & Goodman, L.L.P.
1300 19th Street N.W., Suite 600 Wash. D.C. 20036

Telefonische Auskünfte: (Name und Telefonnummer)

Direct Telephone Calls to: (name and telephone number)

Mark S. Bicks (202) 659-9076

Vor- und Zuname des einzigen oder ersten Erfinders	Full name of sole or first inventor	Armin Wagner
Unterschrift des Erfinders	Inventor's signature	[Signature] Date 7.5.2001
Wohnsitz	Residence	Oberrot, Germany
Staatsangehörigkeit	Citizenship	German
Postanschrift	Post Office Address	Am Relpersberg 2
		D-74420 Oberrot, Germany
Vor- und Zuname des zweiten Miterfinders (falls zutreffend)	Full name of second joint inventor, if any	Claudia Wisinger
Unterschrift des zweiten Erfinders	Second inventor's signature	[Signature] Date 10.05.01
Wohnsitz	Residence	München, Germany
Staatsangehörigkeit	Citizenship	
Postanschrift	Post Office Address	Schopenhauerstrasse 97
		D-80809 München, Germany

(Im Falle dritter und weiterer Miterfinder sind die entsprechenden Informationen und Unterschriften hinzuzufügen.)

(Supply similar information and signature for third and subsequent joint inventors.)

Please type a plus sign (+) inside this box ➡ ☐

PTO/SB/02A (3-97)

Approved for use through 9/30/98, OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION	ADDITIONAL INVENTOR(S) Supplemental Sheet Page <u>1</u> of <u>1</u>
--------------------	---

Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Dieter Michael		Roth	
Inventor's Signature	Dieter Michael Roth		Date 07.05.2001
Residence: City	Gartringen-Rohrau	State	Country Germany
Post Office Address	Hildirzhauser Strasse 31		
Post Office Address			
City	Gartringen-Rohrau	State	Country Germany
ZIP	D-71116	Country	Germany
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Michael		Eigner	
Inventor's Signature	Michael Eigner		Date 16.5.01
Residence: City	Leinfelden-Echterdingen	State	Country Germany
Post Office Address	Kelterrainstrasse 39		
Post Office Address			
City	Leinfelden-Echterdingen	State	Country Germany
ZIP	D-70771	Country	Germany
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle (if any))		Family Name or Surname	
Eckhard		Konig	
Inventor's Signature	Eckhard Konig		Date 7.5.2001
Residence: City	Ehningen	State	Country Germany
Post Office Address	Königsberger Strasse 29		
Post Office Address			
City	Ehningen	State	Country Germany
ZIP	D-71139	Country	Germany

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.